

ENV-003b — Apply Required Configuration Values

[Go to ENV-003 — Establish Controlled Starting State](#)

Statement

Before each [Test Execution](#), the [DIDO-TE](#) SHALL apply each required [Configuration](#) value to the applicable [Test Environment](#) element.

Derived From

- [ENV-003 — Establish Controlled Starting State](#)
- [\[DTE5\] DIDO-TE Requirements Register](#), source requirement identifier and obligation to be assigned
- [\[DTE6\] Structured Information Processing Reference Architecture \(SIP-RA\)](#)
- [\[DTE7\] Federated Data Interpretation Systems Reference Architecture \(FDIS-RA\)](#)

Rationale

Required [Configuration](#) values establish the controlled settings governing the behaviour and interactions of the elements participating in a [Test Execution](#).

Applying each value to its intended [Test Environment](#) element ensures the starting state corresponds to the applicable [Test Definition](#) and controlled descriptive information.

Controlling Configuration values limits unintended variation among repeated Test Executions and supports [Reproducibility](#), [Comparability](#), and interpretation of the resulting [Test Results](#).

Applies To

- [Test Environment](#)
- [Test Definition](#)
- [Test Execution](#)
- [Configuration](#)
- [Test Object](#)
- [Node](#)
- [Test Resource](#)

Verification

Verification confirms that:

- The controlled descriptive information identifies each required Configuration value and its applicable Test Environment element.
- The DIDO-TE applies each required Configuration value before Test Execution.
- Each applied Configuration value corresponds to the value specified by the controlled descriptive information.
- The DIDO-TE excludes unspecified, obsolete, conflicting, and prohibited Configuration values.
- The DIDO-TE records the Configuration values applied to the Test Environment.
- The DIDO-TE maintains [Traceability](#) among each required Configuration value, its applicable Test Environment element, and the applicable Test Execution.
- A missing, incorrect, conflicting, prohibited, obsolete, or untraceable Configuration value constitutes nonconformance with this requirement.

Verification includes:

- Inspection of the controlled descriptive information specifying the required Configuration values
- Inspection of the Configuration values applied to each applicable Test Environment element
- Comparison of the applied values with the specified values
- Testing for the absence of unspecified, obsolete, conflicting, and prohibited Configuration values
- Inspection of the resulting Configuration record
- Inspection of Traceability records connecting each Configuration value to its applicable element and Test Execution
- A negative assessment using a missing, incorrect, conflicting, prohibited, obsolete, or untraceable Configuration value
- Confirmation that the negative assessment produces a nonconformance result

Referenced By

Plugin Backlinks: Nothing was found.

Related Architecture Sections

- Add links to the architecture sections governing Configuration specification, Configuration application, state control, and Test Execution admission.

Delivery Phase

Assign the applicable delivery phase.

Requirement Status

Draft

Statement Reference

Use the following syntax to reference this requirement's Statement section from another DokuWiki page:

```
{{section>dido:03-dido-te:99-annexes:annex-c-requirements:02-test-environment-requirements:env-003-establish-controlled-starting-state:env-003b-apply-required-configuration-values#Statement&noheader&nofooter&noeditbtn}}
```

© 2026 Dido Solutions, Inc. and Jackrabbit Consulting, Inc.

From:
<https://wiki.didosolutions.com/> - Dido Solutions, Inc Wiki

Permanent link:
<https://wiki.didosolutions.com/dido/03-dido-te/99-annexes/annex-c-requirements/03-functional-requirements/03-01-test-environment-requirements/env-003-establish-controlled-starting-state/env-003b-apply-required-configuration-values?rev=1787081664>

Last update: 2026/08/18 12:34

