

Communication Role

[Return to C Terms](#)

Discussion

A Communication Role identifies how a Logical Node participates in a Logical Communication Endpoint.

Communication Roles describe logical participation in an exchange. They do not prescribe communication technology, protocol, deployment topology, or runtime packaging.

A Logical Node performs one or more Communication Roles for a given endpoint. The same Logical Node also performs different Communication Roles across different endpoints. For example, a Logical Node publishes health status, subscribes to configuration updates, consumes commands, and produces acknowledgements.

Definition

Logical participation responsibility performed by a Logical Node at a Logical Communication Endpoint.

Source

Specialization of Node Role and Communication Endpoint from Part 1, Sections 7.4 and 7.6; generalised from publisher, subscriber, command, control-plane, and topic-participation material in the original FX Demo Reference Architecture.

Note

A Communication Role belongs to the logical interaction model. It does not identify a deployed process, network connection, protocol binding, or middleware participant.

Example

A Logical Node performs a Publisher Role when it produces health-status information for a logical health-status endpoint.

[Return to Top](#)

From:
<https://wiki.didosolutions.com/> - **Dido Solutions, Inc Wiki**

Permanent link:
https://wiki.didosolutions.com/dido/99_annexes/annex-b-terms-and-definitions/c/communication_role

Last update: **2026/07/18 12:33**

