

Node Identity

[Return to Terms and Definitions](#)

Discussion

Node Identity uniquely distinguishes a [Node](#) within a defined architectural, logical, implementation, or deployment context. It provides the basis for attribution, authorisation, monitoring, audit, provenance, replay, recovery, and evidence.

A Node Identity allows later parts to identify which Node produced information, consumed a Communication Endpoint, reported status, acknowledged a command, executed a Node Role, or generated evidence.

A Node Identity exists at the architectural level. A deployment profile may associate a Node Identity with a container name, pod name, process identifier, host name, network address, certificate, service account, or other runtime identifier. Those identifiers do not replace the Node Identity.

Definition

identifier uniquely distinguishing a [Node](#) within a defined architectural context

Source

Adapted from FX Demo Reference Architecture, Section 2.1.16, Node Identity; generalised from implementation-profile identity to conceptual architectural identity.

Note

A Node Identity is not a container name, pod name, host name, process identifier, user identity, organisation identity, network address, or repository path.

Example

A Phase 0 implementation profile may assign a stable Node Identity to a health-monitoring [Node](#) so later reviewers can attribute its heartbeat records, status messages, audit entries, and evidence to the same architectural participant.

From:
<https://wiki.didosolutions.com/> - **Dido Solutions, Inc Wiki**

Permanent link:
https://wiki.didosolutions.com/dido/99_annexes/annex-b-terms-and-definitions/n/node_identity?rev=1783793707

Last update: **2026/07/11 11:15**

